

## Scissor Lift

Used Scissor Lift Texas - Scissor lifts are industrial equipment that relies on steel linked arms to lift vertically. This equipment is utilized to create an “X” patterned support in order to accomplish vertical lifting. There is a rectangular platform that is attached to the top of the scissor lift. To maintain operator safety, there are support railings at the top of the platform. This machine maintains a low profile that is ideal for hard surfaces such as concrete and other compact surfaces. This equipment relies on either a combustion engine or an electric motor to create the lift and transport the machine. The lift function operates on a vertical plane only. In order for the operator to transport the lift horizontally, they will have to reposition the lift itself. The same lifting technology is used for the lifting components in regular scissor lift models as well as rough terrain models. The rough terrain units are designed for driving on gravel and uneven surfaces. Higher ground clearance and oversized all-terrain tires enable these machines to travel to tricky locations. Some scissor lifts have 4WD to travel through difficult and muddy locations. Thanks to the higher center of gravity lower lifting heights are available. If you have never operated one before, scissor lifts can seem strange or intimidating. Images of swaying in the wind and being precariously balanced may come to mind. Feel secure knowing you will not feel the lift even moving and you will be in a stable position. A variety of safety tests have to be completed before this unit can be sold. Of course, if you are new to this kind of equipment, it is normal to feel unsure until you familiarize yourself with the unit. It is essential to maintain safety precautions all of the time. Understanding what you will be using your scissor lift for will help ensure you have the right type of model. The scissor lift model you will need will largely depend on the types of jobs you will need to do. How high you need to travel and how heavy the loads you will be transporting are all key factors. There are specific models available to take you to extreme heights. Smaller models are commonly used for interior applications including warehouses and freight or factory settings. If you do not need the highest capacity model, there is no need to choose the largest unit available. There are extra platforms and railings available to provide additional safety measures. Scissor lifts are reliable and safe for a multitude of applications. If these machines did not follow strict safety rules and particular inspections, they would not be for sale across the globe. Scissor lifts help people accomplish tasks that are otherwise unattainable, unreachable or inaccessible. These machines are situated in place before elevating vertically. Before the lift is engaged, the operator will properly position the unit. There are a variety of safety features incorporated into the design. Following operational guidelines is essential for everyone’s safety. There is a safe basket workspace on scissor lifts to ensure lifting tasks are more secure as opposed to hanging off of scaffolding or a ladder. Most scissor lifts rely on internally mounted batteries within the lifts’ base for power. After working an extensive shift or for prolonged periods of time, charging is necessary. Batteries may be changed every 12 hours or charged many times throughout the day. To charge the scissor lift, the operator parks it close to an electrical outlet within a well-ventilated location. When the machine is parked, the emergency shut-off switch becomes engaged to stop. The sizeable red button found inside of the basket or the lift located near the charger or control box is the emergency shut-off switch. The battery charger is commonly located on the right side of the lift on the base. Many older models may feature the battery charger mounted on the back of the scissor lift. The scissor lift charger is plugged into the AC extension cord into a well-ventilated location. Next, the extension cord plugs into an electrical outlet. The length of the electrical cord on the battery charger needs to be short to prevent damage or running over it. There is a high possibility for extreme danger if excess extension cord length dropped out of the battery charger storage area during operation. Once the scissor lift is plugged in, all of the lights on the charger should ideally become illuminated. The batteries will automatically begin charging once plugged in. The battery lights will switch to green once complete charging has occurred and the charger will shut off. Models that are older and rely on a meter will show zero volts after they are charged fully and then the charger will

also turn off automatically. After the batteries are completely charged the scissor lift can complete another shift. Many places employ their scissor lift for 24 hours a day by having additional batteries continually charging.